

## Specification Sheet

Part Number: T30RA30



Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 103-00002  |
| <b>Type</b>                    | T30RA  |
| <b>Color</b>                   | Natural (NA)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.</li><li>• Available in reels of 3,000 each or bandoliers of 30 each.</li></ul> |
| <b>Quantity Per</b>            | bag  |
| <b>Product Description</b>     | Cable ties for use with HellermannTyton's AT2060 automatic cable tie tool  |
| <b>Short Description</b>       | Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg   |
| <b>Global Part Name</b>        | T30RA-PA66-NA  |

|  |         |
|--|---------|
| <b>Minimum Tensile Strength (Imperial)</b> | 30.0    |
| <b>Minimum Tensile Strength (Metric)</b>   | 133.4   |
| <b>Length L (Imperial)</b>                 | 6.0     |
| <b>Length L (Metric)</b>                   | 152.4   |
| <b>Identification Plate Position</b>       | none    |
| <b>Reel Diameter (Imperial)</b>            | 17.7    |
| <b>Reel Diameter (Metric)</b>              | 450.0   |
| <b>Reel Width (Imperial)</b>               | 7.197   |
| <b>Reel Width (Metric)</b>                 | 182.8   |
| <b>Voltage Range</b>                       | 27 Volt |
| <b>Releasable Closure</b>                  | No      |
| <b>Width W (Imperial)</b>                  | 0.14    |
| <b>Width W (Metric)</b>                    | 3.6     |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06    |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5     |
| <b>Bundle Diameter Max (Imperial)</b>      | 1.25    |
| <b>Bundle Diameter Max (Metric)</b>        | 31.75   |

**Cycle Time** 1.2 seconds

**Power Supply** Electrical

**Tension Force** Adjustable

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**US MIL SPEC** MS3367-5-9

SAE-AS33671

**Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Certification/Specification WEB**

CAGE Code 53421 UL-ZODZ2.E64139

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)** 600

**Package Quantity (Metric)** 600

**Customs Number** 3926909987

**Weight (Metric)** 1.8

**Weight (Imperial)** 3.9

**Reel Weight (Imperial)** 7

**Reel Weight (Metric)** 3.175